



Karta techniczna produktu

Chemmot Ewa Kumorek spółka komandytowa
PL 32-050 Skawina, ul. Józefa Piłsudskiego 59

Telefon: 12 276 75 45
Telefax: 12 276 78 20

DECO COLOR® znak towarowy CHEMMOT®
DECO COLOR® najlepiej postrzegany brand farb i lakierów w aerozolu

Trade name	
MILITARY PAINT by DECO COLOR® aerosol line	
Article No	
281 001, 281 019, 286 003, 286 014, 286 031, 287 013, 287 016, 287 038, 288 027, 289 010; 289 021	
Seller/Manufacturer	
Chemmot Ewa Kumorek spółka komandytowa; Józefa Piłsudskiego 59, 32-050 Skawina, Polska	
Product's description	
<p>Anti-reflective paint used as well to military camouflage, as to renovate military equipment. Wide range of application in masking on hunting, but most of all to mask the equipment in very popular ASG games like MilSim.</p> <p>Due to specially selected colours of Military Paint you are able to make a professional camouflage of your military equipment or make its renovation.</p>	
Main features	
<p>Notice: Paint is compatible with all paint systems (alkyd, acryl, nitro-combination) water and solvent based.</p> <p>High adhesive Short drying time up to 8 minutes! Touch dry: 15-20 min; Hardened: 10-14 h Efficiency 1,5-2 m² depending on colour and type of surface by one application Matt finish of painted surface Variety of 11 most common colours of military camouflage For indoor and outdoor use Capacity 400 ml</p>	
Physical and Chemical Properties	
Capacity	400 ml
Base/resin	nitro-synthetic resin
Colour	RAL numbers
Gloss	semi gloss
Application temperature	15-25°C
Dust free	5-8 min
Touch free	15-20 min
Hardened	10-14h
Cover capacity	1,5-2 m ² depending on colour and type of surface by one application
High temperature resistance	up to 100°C
VOC content	about 80%
Solids content	about 20%
Petrol resistance	good
Alcohol resistance	limited
Primer usage	not applicable
Other coating applying	possible



Karta techniczna produktu

Chemmot Ewa Kumorek spółka komandytowa
PL 32-050 Skawina, ul. Józefa Piłsudskiego 59

Telefon: 12 276 75 45
Telefax: 12 276 78 20

DECO COLOR® znak towarowy CHEMMOT®
DECO COLOR® najlepiej postrzegany brand farb i lakierów w aerozolu

Usage

Before application read carefully instructions on the container and use according to the manufacturer's recommendations.

Recommended substrate conditions

Proper surface preparation has huge influence to final result. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and let it dry.
Primed surface should be grinded with fine-grained abrasive paper previously.
Compatible with all paint systems (alkyd, acrylic, nitro-combination) water and solvent based as well.

Method of use

Apply product at temperature about 15-25°C (optimum temperature for good varnish drying).
Drying time depends also on air humidity and product density.
Painting should be made in well ventilated room.
Prior to commencing painting, shake the container for about one minute, what helps mix the varnish by the ball inside.
Perform the test spray.
Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimetres.
Wait few minutes between each layer when applying.
When finished, clean the nozzle.
Put the container upside down, pressing the nozzle for the period of three seconds.

Technical Data Sheet version 05 from 01/03/2022