



Karta techniczna produktu

Chemmot Ewa Kumorek spółka komandytowa
PL 32-050 Skawina, ul. Józefa Piłsudskiego 59

Telefon: 12 276 75 45
Telefax: 12 276 78 20

DECO COLOR® znak towarowy CHEMMOT®
DECO COLOR® najlepiej postrzegany brand farb i lakierów w aerozolu

Trade name	
RUST BLOCKER by DECO COLOR® aerosol line	
Article No	
18 300; 18 400; 18 500; 18 600; 18 700; 18 800; 18 900; 18 950	
Seller/Manufacturer	
Chemmot Ewa Kumorek spółka komandytowa; Józefa Piłsudskiego 59, 32-050 Skawina, Polska	
Product's description	
Professional protective coating for metals. 4in1 properties: <ol style="list-style-type: none">1. perfect adhesive primer2. active corrosion protection technology LCI (blocks process of oxidation)3. fast drying paint with exceptional covering power4. effective protection against environmental influences 360° FUN nozzle allows applying in different positions by wide and narrow stream	
Main features	
Active rust protection system prevents corrosion process and it's further spread Protects against environmental influences Protection technology LCI Very good covering 8 most common colours For indoor and outdoor use CFC free	
Physical and Chemical Properties	
Capacity	400 ml
Base/resin	alkyd modified resin
Colour	RAL numbers
Gloss	semi mat
Application temperature	15-25°C
Dust free	up to 8 min
Touch free	15-20 min
Hardened	10-14 h
Cover capacity	1,5-2 m ² depending on colour and type of surface by one application
High temperature resistance	up to 100°C
VOC content	about 70%
Solids content	about 30%
Petrol resistance	good
Alcohol resistance	limited



Karta techniczna produktu

Chemmot Ewa Kumorek spółka komandytowa
PL 32-050 Skawina, ul. Józefa Piłsudskiego 59

Telefon: 12 276 75 45
Telefax: 12 276 78 20

DECO COLOR® znak towarowy CHEMMOT®
DECO COLOR® najlepiej postrzegany brand farb i lakierów w aerozolu

Primer usage	n/a
Other coating applying	n/a
Usage	
Before application read carefully instructions on the container and use according to the manufacturer's recommendations.	
Recommended substrate conditions	
Proper surface preparation has huge influence to final result. Fundamental principle, which relate to all surfaces prepared to painting is to grind, degrease and let it dry. Primed surface should be grinded with fine-grained abrasive paper previously. Notice. For surfaces made of PUR, PS, PA, EPDM, ABS, GfK, Hart – PCV use Plastic Primer DECO COLOR previously.	
Method of use	
Apply product at temperature about 15-25°C (optimum temperature for good varnish drying). Drying time depends also on air humidity and product density. Painting should be made in well ventilated room. Prior to commencing painting, shake the container for about one minute, what helps mix the varnish by the ball inside. Perform the test spray. Apply the varnish with few thin layers rather than one thick layer, from the distance of 25-30 centimetres. Wait few minutes between each layer when applying. When finished, clean the nozzle. Put the container upside down, pressing the nozzle for the period of three seconds.	
Technical Data Sheet version 05 from 01/03/2022	